

PRODUCT DATA SHEET

ISO-TOP CLEANEX



illustration purposes only

PRODUCT DESCRIPTION

ISO-TOP CLEANEX has been specially developed for cleaning the inside of PUR spray foam guns. In addition, it is also very suitable for removing fresh, still moist, non-cured PUR soiling from various metal, polymer and timber surfaces.

In addition, ISO-TOP CLEANEX can be used in small quantities as an expansion accelerator for pre-compressed, impregnated joint sealing tapes. For this purpose, the tape is sprayed with ISO-TOP CLEANEX after installation in the joint.

ISO-TOP CLEANEX can be applied directly from the can using the spray head attached or be screwed to the PUR spray foam guns.

APPLICATION

For cleaning the inside and outside of PUR foam guns and for removing fresh soiling caused by 1-component gun spray foam.

PACKAGING

12 cans (of 500 ml) per box

PRODUCT ADVANTAGES

- specially matched to 1-component PUR spray foam
- soiling caused by fresh PUR foam is loosened easily and can be removed directly
- very good residue-free cleaning of foam sticking to the inside of the gun
- straightforward handling using versatile screw flange and / or spray head attachment
- compatible with most foam gun types
- expansion accelerator for pre-compressed, impregnated joint sealing tapes

ISO-TOP CLEANEX

| Technical data | Standard | Classification |
|---------------------|----------|--|
| Form | | aerosol |
| Colour | | colourless |
| Odour | | characteristic |
| Shelf life | | max. 24 months in the original, unopened packaging |
| Storage temperature | | +5°C to +25°C |

PROCESSING

As PUR cleaner

After use of 1-component PUR spray foam application guns, clean the gun of soiling inside and out by spraying it with cleaner.

To do this, first clear the screw flange on the foam gun of fresh foam residue by spraying it with cleaner. Then screw the cleaner onto the gun, hold the container upwards, open the pressure valve (dosing screw) on the gun fully and spray cleaning fluid through it until no more foam residue comes out of it. Wait for 1 minute, repeat the cleaning procedure, close the dosing screw again. The foam gun can remain on the cleaner can until it is required again.

We recommend that you wear safety goggles and gloves for this work. Before application, check compatibility with the surface. For further information, see the safety data sheet which is available on request.

As an expansion accelerator

At very low temperatures, small dimensions of pre-compressed, impregnated joint sealing tapes only expand very slowly. After fitting in the construction joint they can be sprayed directly with a thin layer of ISO-TOP CLEANEX. This accelerates the expansion process. Adjacent surfaces, particularly painted or stained surfaces, must be protected.